

RIGID CLICK

FEATURES	STANDARD	PLANKS	HERRINGBONE	TILES
Floorcovering	EN 649	Heterogeneous LVT floorcovering	Heterogeneous LVT floorcovering	Heterogeneous LVT floorcovering
Finishing		matt PU lacquer	matt PU lacquer	matt PU lacquer
Design		Wood	Wood	Concrete
Embossing		C3020 C3030 <i>Universal Embossed</i> C4010 C4030 C4050 C4070 C12041 C12042 C15011 C15012 C15051 C15052 C15053 C15054 C15055 C70010 C70040 <i>Registered Embossed</i>	C6032 C6033 C6041 C6042 C7001 C7004 <i>Universal Embossed</i> C7011 C7012 C7551 C7552 C7553 C7554 7C555 <i>Registered Embossed</i>	Universal Embossed
Colours		17	13	6
Dimension	EN 427	22x121 cm 3020 3030 4010 4030 4050 4070 12041 12042 70010 70040 23x152 cm 15011 15012 15051 15052 15053 15054 15055	15x75 cm	45x90 cm
Bevelling		All sides	All sides	All sides
Content		6 pieces (1,617 m ²) 120x24 cm 6 pieces (2,139 m ²) 150x24 cm	10 pieces (1,080 m ²)	4 pieces (1,638 m ²)
Weight	EN 430	ca. 9600 g/m ²	ca. 9600 g/m ²	ca. 9600 g/m ²
Thickness	EN 428	6,0 mm	6,0 mm	6,0 mm
Thickness PU	EN 429	0,55 mm	0,55 mm	0,55 mm
Classification	EN 685	23, 34	23, 34	23, 34
Fire classification	EN 13501	Bfl-S1	Bfl-S1	Bfl-S1
Slipresistance	DIN 51130 EN 13893	R9 DS	R9 DS	R9 DS
Weargroup	EN 649	T	T	T
Residual indentation	EN 433	< 0,1 mm	< 0,1 mm	< 0,1 mm
Dimension stability	EN 434	< 0,10%	< 0,10%	< 0,10%
Soundreduction	EN140-8	ca. 11 dB(A)*	ca. 11 dB(A)*	ca. 11 dB(A)*
Thermal conductivity	EN12667 DIN 52612	0,02 m ² k/w	0,02 m ² k/w	0,02 m ² k/w
Electrical conductivity	EN 1081	app 10 ¹¹ Ohm	app 10 ¹¹ Ohm	app 10 ¹¹ Ohm
Suitable for castor chairs	EN 425	Yes, type W	Yes, type W	Yes, type W
Floor heating	EN14041	Yes, max. 27°C	Yes, max. 27°C	Yes, max. 27°C
Colourfastness	ISO 105-B02	6> Grade	6> Grade	6> Grade
Resistance to chemicals	EN 423 EN ISO 26987	Yes, see 1	Yes, see 1	Yes, see 1
Odor control	ISO 16000-28	Suisse Norm SNV	Suisse Norm SNV	Suisse Norm SNV
AgBB VOC test		Approved	Approved	Approved
REACH regulation (EC)		1907/2006	1907/2006	1907/2006
CE, AGBB, Dibt, Eurofins, Floorscore, A+, ISO9001, ISO14001		Yes	Yes	Yes

¹ Resistance depending on concentration and exposure time, with prolonged action of oils, fats, acids, alkalis and other aggressive chemicals please contact us.

* In combination with Redfloor

