

CLASSIC SERIES

FEATURES	STANDARD	PLANKS	HERRINGBONE
Floorcovering	EN 649	Heterogeneous LVT floorcovering	Heterogeneous LVT floorcovering
Finishing		PU-Lack super mat	PU-Lack super mat
Design		Wood	Wood
Embossing		Registered Embossed	Registered Embossed
Colours		6	6
Measurement	EN 427	151,68x24,13 cm	74,93x14,98 cm
Bevelling		All sides	All sides
Content		10 pieces (3,660 m ²)	26 pieces (2,918 m ²)
Article numbers		15121 15122 15123 15124 15125 15126	7521 7522 7523 7524 7525 7526
Weight	EN ISO 23997	ca. 4310 g/m ²	ca. 4310 g/m ²
Thickness	EN ISO 24346	2,5 mm	2,5 mm
Wearlayer	EN ISO 24340	0,55 mm	0,55 mm
Classification	EN ISO 10874	23, 33, 42	23, 33, 42
Fire classification	EN 13501-1	Bfl-S1	Bfl-S1
Slip resistance	DIN 51130 EN 13893	R10 DS	R10 DS
Weargroup	EN 649	T	T
Residual indentation	EN ISO 24343-1	< 0,1 mm	< 0,1 mm
Dimension stability	EN ISO 23999	< 0,25%	< 0,25%
Sound absorption	EN ISO 10140-3	ca. 3 dB(A)	ca. 3 dB(A)
Thermal conductivity	EN12664 DIN 52612	0,091 (W/(m*K))	0,091 (W/(m*K))
Electrical conductivity	EN 1081	app 10 ¹¹ Ohm	app 10 ¹¹ Ohm
Suitable for castor chairs	EN ISO 4918	Yes, type W	Yes, type W
Floor heating		Yes, max. 27°C	Yes, max. 27°C
Colourfastness	ISO 105-B02	6> Grade	6> Grade
Resistance to chemicals	EN 423 EN ISO 26987	Yes, see ¹	Yes, see ¹
Odor control	ISO 16000-28	Suisse Norm SNV	Suisse Norm SNV
AgBB VOC test		Approved	Approved
REACH regulation (EC)		1907/2006	1907/2006
CE, AGBB, Dibt, Eurofins, Floorscore, A+, ISO9001, ISO14001		Yes	Yes

¹ Resistance depending on concentration and exposure time, with prolonged action of oils, fats, acids, alkalis and other aggressive chemicals please contact us.

