

RIGID CLICK

FEATURES	STANDARD	PLANKS	HERRINGBONE	CHEVRON	TILES
Floorcovering	EN 649	Heterogeneous LVT floorcovering	Heterogeneous LVT floorcovering	Heterogeneous LVT floorcovering	Heterogeneous LVT floorcovering
Afwerking		matt PU lacquer	matt PU lacquer	matt PU lacquer	matt PU lacquer
Design		Wood	Wood	Wood	Stone
Embossing		Universal / C3020 / C3030 Registered / C4010 / C4030 / C4050 / C4070 / C12041 / C12042 / C15011 / C15012 / C15072 / C15073 / C15074 / C15075 / C15080 / C15081 / C15082 / C15083 / C15084 / C15085 / C70010 / C70040	Universal / C6032 / C6033 / C6041 / C6042 / C7001 / C7004 Registered / C7011 / C7012 / C7572 / C7573 / C7574 / C7575 / C7580 / C7581 / C7852 / C7853 / C7854 / C7585	Universal / C6541 / C6542 Registered / C6580 / C6581 / C6582 / C6583 / C6584 / C6585	Universal Embossed
Colours		22	18	8	6
Dimension	EN 427	121,30x22,20 cm / C3020 / C3030 / C4010 / C4030 / C4050 / C4070 / C12041 / C12042 / C70010 / C70040 151,80x23,60 cm / C15011 / C15012 / C15051 / C15052 / C15053 / C15054 / C15055 151,76x24,13 cm / C15080 / C15081 / C15082 / C15083 / C15084 / C15085	14,50x74,30 cm	66,55x14,50 cm	45,10x90,80 cm
Bevelling		All sides	All sides	All sides	All sides
Content		6 pieces (1,617 m ²) / 121,5x22 cm 6 pieces (2,139 m ²) / 152x23,5 cm 6 pieces (2,197 m ²) / 152x24 cm	10 pieces (1,080 m ²) 12 pieces (1,293 m ²) / C7580 t/m C7585	12 pieces (1,158 m ²)	4 pieces (1,638 m ²)
Weight	EN 430	ca. 9600 g/m ²	ca. 9600 g/m ²	ca. 9600 g/m ²	ca. 9600 g/m ²
Thickness	EN 428	6,0 mm	6,0 mm	6,0 mm	6,0 mm
Thickness PU	EN 429	0,55 mm	0,55 mm	0,55 mm	0,55 mm
Classification	EN 685	23, 34	23, 34	23, 34	23, 34
Fire classification	EN 13501	Bfl-S1	Bfl-S1	Bfl-S1	Bfl-S1
Slipresistance	DIN 51130 EN 13893	R10 DS	R10 DS	R10 DS	R10 DS
Weargroup	EN 649	T	T	T	T
Residual indentation	EN 433	< 0,1 mm	< 0,1 mm	< 0,1 mm	< 0,1 mm
Dimension stability	EN 434	< 0,10%	< 0,10%	< 0,10%	< 0,10%
Soundreduction	EN140-8	ca. 11 dB(A)*	ca. 11 dB(A)*	ca. 11 dB(A)*	ca. 11 dB(A)*
Thermal conductivity	EN12667 DIN 52612	0,02 m ² k/w	0,02 m ² k/w	0,02 m ² k/w	0,02 m ² k/w
Electrical conductivity	EN 1081	app 10 ¹¹ Ohm	app 10 ¹¹ Ohm	app 10 ¹¹ Ohm	app 10 ¹¹ Ohm
Suitable for castor chairs	EN 425	Yes, type W	Yes, type W	Yes, type W	Yes, type W
Floor heating	EN14041	Yes, max. 27°C	Yes, max. 27°C	Yes, max. 27°C	Yes, max. 27°C
Colourfastness	ISO 105-B02	6> Grade	6> Grade	6> Grade	6> Grade
Resistance to chemicals	EN 423 EN ISO 26987	Yes, see 1	Yes, see 1	Yes, see 1	Yes, see 1
Odor control	ISO 16000-28	Suisse Norm SNV	Suisse Norm SNV	Suisse Norm SNV	Suisse Norm SNV
AgBB VOC test		Approved	Approved	Approved	Approved
REACH regulation (EC)		1907/2006	1907/2006	1907/2006	1907/2006

CE, AGBB, Dibt, Eurofins, Vloerscore, A+, ISO9001, ISO14001

*Resistance depending on concentration and exposure time, with prolonged action of oils, fats, acids, alkalis and other aggressive chemicals please contact us.

* In combination with Redfloor

